



D5583-1 RADIUS BLOCK

NOTES:

- 1) MATERIAL: 6061-T6/T62 ALUMINUM SHEET, 0.125 THICK
PER QQ-A-250/11 OR AMS-QQ-A-250/11
OR AMS 4025 OR AMS 4027 OR ASTM B209
REF DART SPEC M6061T6S
OR: 6061-T6/T651/T6510/T6511/T62 ALUMINUM BAR
PER QQ-A-225/8 OR AMS-QQ-A-225/8 (OR AMS 4117/4128/4115/4116) OR
QQ-A-200/8 OR AMS-QQ-A-200/8 (OR AMS 4160) OR ASTM B211 OR ASTM B221
REF DART SPEC M6061T6B
- 2) FINISH: ANODIZE PER MIL-A-8625, TYPE II, CLASS 2, COLOR = BLACK
PRIME GREY PER QSI 005, 4.2.1.3.2
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: IDENTIFY PER QSI 044 6.1
- 7) WEIGHT: 0.01 lbs

RELEASED
2018 MAR 07
ENC-593

APPROVED

A	NEW ISSUE	RF	17.11.01
REV.	DESCRIPTION	BY	DATE
DESIGN	AJS	DART AEROSPACE USA, INC.	
DRAWN	RF	EUGENE, OR	
CHECKED	VS	DRAWING NO.	REV. A
MFG. APPR.	JFS	D5583	SHEET 1 OF 1
APPROVED	HS	TITLE	SCALE
DE APPR.	CP	RADIUS BLOCK	NTS
DATE	17.11.01	COPYRIGHT © 2017 BY DART AEROSPACE USA, INC. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.	